

Care and cleaning of Recacril® canvas AWNINGS AND MARINE FABRICS

The **Infinity Process**, a high technology finish, provides **Recacril®** with a long lasting protection against mold and mildew, excellent water and oil repellency, and protects you from both sun and water for many years.

However, the accumulation of dust, pollution particles, foreign organic materials, and general dirt can damage this protection, shortening the life of the **Recacril®** so they should be removed.

The most effective method for maintaining **Recacril®** is to clean the canvas once a month with water using a low pressure hose, thereby reducing dirt accumulation.

It is very important that after cleaning with water, the canvas be allowed to completely dry before rolling back a retractable awning.

When it rains, you can leave the awning open if the frame and pitch allows, since the rain helps wash away dirt. If for any reason you have to roll the wet awning, it must be unrolled as soon as possible to let it dry. In times of continuous rains it is advisable to keep the awnings rolled up.

If periodic washing with water is done, in most environments, you should only need to do a more thorough cleaning every 2 or 3 years.

Normal cleaning:

1. Brush off dust and dirt with a soft brush. **NEVER** brush with stiff brushes since this can damage the fabric finish.
2. Spray the awning with clean water. If a hose is used, to avoid high pressure.

3. Prepare a solution of solvent-free soap in warm water (no more than 40°C) and apply it on the fabric.
4. Scrub with a soft brush allowing the solution penetrate the fabric.
5. Rinse with water to remove all traces of soap.
6. Let air dry and do not wind, close the awning until the canvas is completely dry.

Recacril® is highly resistant to the growth of fungus, mold, and mildew, however they can grow on embedded dirt. To clean these stains, follow these more intensive cleaning procedures:

Intensive cleaning:

1. Brush off dust and dirt with a soft brush. **NEVER** brush with stiff brushes since it could damage the finish and fabric.
2. Prepare a solution with 10% household bleach, 20% of solvent-free neutral detergent and 70% water.
3. Apply the solution on the fabric, allowing to remain between 15 and 20 minutes maximum.
4. Rinse with clean water several times. Bleach residues remaining on canvas combined with the sun could damage the fabric.
5. Allow to air dry and do not wind, close the awning until the canvas is completely dry.
6. Repeat the process if necessary.

To protect the environment, be sure to contain and dispose of the dirty water when using bleach as it can be harmful to animals and plants.

Recacril® canvas Warranty Certificate

For **10 years** after installation, **RECASENS** warranty covers only the rot-resistant properties and color fastness of the **Recacril®** fabrics when regularly maintained, and under normal use and environment.

RECASENS will either replace free of charge, or reimburse the invoice value of the section of **Recacril®** fabric recognized as faulty, excluding any costs or any other compensation for any reason whatsoever.

The **WARRANTY** does not protect against any damage due to abuse, neglect, vandalism, burns of any kind, fires and natural disasters.

Consequently there is **no** cover for:

- Faulty maintenance or the use of unsuitable products or instruments: no detergent, chemical product or solvent can be used, **NOR** any scraper or other instrument that may damage the surface of the **Recacril®** fabric.
- Defects due to the aging and normal wear of the fabric.
- Atmospheric or phytosanitary pollution.
- Soiling caused by animals.

- The repair of damage or defects in the fabric resulting from accidents or negligence not attributable to **RECASENS** or resulting from force majeure.
- Faulty assembly or handling by the user, the projection of various products, hanging objects on the fabric, falling objects, bumps, road accidents, vandalism, burns from cigarettes or other sources.
- Lightning or unusual climatic or environmental conditions.

The **WARRANTY** excludes the cost of any mechanical device (hardware, mechanisms, structures, etc.) as well as any cost of manufacturing, assembly and installation.

The **WARRANTY** takes effect from the date of installation of awnings, curtains or any other product made with **RECASENS** canvases.

Recacril® fabric is usually a component of the final product. If you detect any defective fabric, please contact your installer or distributor from whom you purchased the product.

8/2022

Phone: **610-897-8156**

Fax: **610-677-1605**

Email: customerservices@recasensusa.com



RECASENS USA
BCN 1886

We're woven differently